

Datasheet

FUJITSU Image Scanner fi-7180

Compact ADF scanner offers best performance out of its class



The fi-7180 scans A4 portraits at 80 ppm/160 ipm (200/300 dpi), loads up to 80 sheets at a time, and ensures utmost efficiency with best-of-class* scanning performance.

Assistance for safe and reliable scanning

The fi-7180 possesses diverse stable paper feeding mechanisms, ensuring speedy and high quality scanning without relying on PC performance. Minimize risk of document damage with Paper Protection function detecting anomalies in sound and monitoring paper feed distance. And bid farewell to missing edges with the scanner's Skew Reducer mechanism. Potential information loss, resulting from multiple sheets being fed through the scanner at once, is also no longer an issue with Ultrasonic Multi-feed detection.

Boosted usability with a user-friendly and compact design

The scanner's compact design is suitable for use anywhere: on desks, in back offices, and inside small companies. Start scanning with a single push of a button. Keep track of scanner operations such as document scanning settings, number of sheets scanned, as well as any existing error statuses, using the LCD operation panels. Daily maintenance tasks, including interior cleaning and roller replacement, can also be done with ease for long-lasting utilization.

High quality images in any condition

Enjoy sharp, high quality images with the fi-7180's CCD image sensors. Subtle changes in scanning environment, such as in air temperature and LED illumination, are also no longer a need for concern with the scanner automatically changing background colors to maintain consistently crisp images.

Advanced software for maximized efficiency

Bypass the inconvenience of making fine adjustments to OCR settings with the PaperStream IP scanner driver, supporting both TWAIN and ISIS. The software automatically converts scanned images into exceptionally clean images, supporting OCR accuracy even when scanning documents with background patterns or wrinkled and soiled documents. Seamlessly linked to PaperStream IP, PaperStream Capture offers various batch scanning capture features to effectively and efficiently feed information into your organization workflow. Automatically utilizing data extracted from barcodes (2D included) and patch codes, the software also determines your preferred saving destinations and eliminates time allocated to routine tasks.

*Based on PFU's investigation performed as of August 31st, 2013 for A4 ADF type document scanners between US\$1,500 - \$3,999.

Technical Information

| | |
|---|---|
| Scanner Type | ADF (Automatic Document Feeder), Duplex |
| Scanning Speed* ¹ (A4 Portrait) (Color* ² /Grayscale* ² /Monochrome* ³) | Simplex: 80 ppm (200/300 dpi) Duplex: 160 ipm (200/300 dpi) |
| Image Sensor Type | Color CCD x 2 (front x 1, back x 1) |
| Light Source | White LED Array x 2 (front x 1, back x 1) |
| Optical Resolution | 600 dpi |
| Output Resolution* ⁴ (Color / Grayscale / Monochrome) | 50 to 600 dpi (adjustable by 1 dpi increments), 1,200 dpi (driver)* ⁵ |
| Output Format | Color: 24-bit, Grayscale: 8-bit, Monochrome: 1-bit |
| Background Colors | White / Black (selectable) |
| Document Size | |
| Maximum* ⁶ | 216 x 355.6 mm (8.5 x 14 in.) |
| Minimum | 50.8 x 54 mm (2 x 2.1 in.) |
| Long Page Scanning* ⁷ (Maximum) | 5,588 mm (220 in.) |
| Paper Weight (Thickness) | |
| Paper | 27 to 413 g/m ² (7.2 to 110 lb)* ⁸ |
| Plastic Card | 1.4 mm (0.055 in.) or less* ^{9,10} |
| ADF Capacity* ^{11,12} | 80 sheets (A4 80 g/m ² or Letter 20 lb) |
| Expected Daily Volume* ¹³ | 11,000 sheets |
| Multifeed Detection | Overlap detection (Ultrasonic sensor), Length detection |
| Paper Protection | Lag detection, Sound detection (iSOP)* ¹⁴ |
| Interface* ¹⁵ | USB 3.0 / USB 2.0 / USB 1.1 |
| Power Requirements | AC 100 to 240 V ±10 % |
| Power Consumption | |
| Operating Mode | 42 W or less |
| Sleep Mode | 1.8 W or less |
| Auto Standby (Off) Mode | Less than 0.35 W |
| Operating Environment | |
| Temperature | 5 to 35 °C (41 to 95 °F) |
| Relative Humidity | 20 to 80% (non-condensing) |

| | |
|---|--|
| Environmental Compliance | ENERGY STAR®, RoHS |
| Dimensions* ¹⁶ (Width x Depth x Height) | 300 x 170 x 163 mm (11.8 x 6.7 x 6.4 in.) |
| Weight | 4.2 kg (9.3 lb) |
| Supported Operating System | Windows® 11, Windows® 10, Windows® 8.1, Windows® 7, Windows Server® 2022, Windows Server® 2019, Windows Server® 2016, Windows Server® 2012 R2, Windows Server® 2012, Windows Server® 2008 R2, Windows Server® 2008* ¹⁷ , macOS, Linux (Ubuntu) |
| Included Software / Drivers | PaperStream IP Driver (TWAIN/TWAIN x64/ISIS), WIA Driver* ¹⁸ , Image Scanner Driver for macOS (ICA)* ^{18,19} , Image Scanner Driver for Linux (SANE)* ^{18,19} , PaperStream Capture, PaperStream ClickScan* ¹⁹ , Software Operation Panel, Error Recovery Guide, ABBYY FineReader for ScanSnap™* ¹⁹ , Scanner Central Admin, 2D Barcode for PaperStream* ¹⁹ |
| Image Processing Functions | Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, Dither, De-Screen, Emphasis, Dropout color (None/Red/Green/Blue/White/Saturation/Custom), sRGB output, Hole punch removal, Index tab cropping, Split image, De-Skew, Edge filler, Vertical streaks reduction, Cropping, Static threshold |
| Included Items | ADF paper chute, AC cable, AC adapter, USB cable, Setup DVD-ROM |

Options

| | | |
|--|--------------|--|
| Post Imprinter (FI-718PR) | PA03670-D201 | Back-side printing on document |
| Carrier Sheets | PA03360-0013 | Each package contains 5 carrier sheets |
| PaperStream Capture Pro Scan Station (DP) | PA43404-A675 | PaperStream Capture Pro optional license |

Consumables

| | | |
|-----------------|--------------|---|
| Brake Roller | PA03670-0001 | Every 200,000 sheets or one year |
| Pick Roller | PA03670-0002 | Every 200,000 sheets or one year |
| Print Cartridge | CA00050-0262 | 4,000,000 printed characters or 6 months after opening the bag |

*¹ Actual scanning speeds are affected by data transmission and software processing times. *² Indicated speeds are from using JPEG compression. *³ Indicated speeds are from using TIFF CCITT Group 4 compression. *⁴ Selectable maximum resolution may vary depending on the length of the scanned document. *⁵ Limitations may apply to the size of documents that can be scanned, depending on system environment, when scanning at high resolution (over 600 dpi). *⁶ Scans folded documents of up to 297 x 432 mm (11.7 x 17 in.) with carrier sheet scanning. *⁷ Capable of scanning documents longer than A4 (210 x 297 mm / 8.3 x 11.7 in.) sizes. When using PaperStream IP (TWAIN/ISIS) to scan at 200 dpi, the maximum scanning length is 5,588 mm (220 in.). *⁸ Thicknesses of up to 127 to 209 g/m² (34 to 56 lb) can be scanned for A8 (52 x 74 mm / 2.1 x 2.9 in.) sizes. *⁹ Capable of scanning up to 1.25 mm (0.049 in.) when scanning in landscape orientation at 300 dpi (80 ppm). *¹⁰ Capable of scanning up to 3 cards at a time (Note: does not set more than one embossed card at a time). *¹¹ Maximum capacity depends on paper weight and may vary. *¹² Capable of setting additional documents while scanning. *¹³ Numbers are calculated using scanning speeds and typical hours of scanner use, and are not meant to guarantee daily volume or unit durability. *¹⁴ Intelligent Sonic Paper Protection. *¹⁵ Connection with USB 3.0 / 2.0 requires the USB port and hub to support USB 3.0 / 2.0. Also note that scanning speed slows down when using USB 1.1. *¹⁶ Excludes the ADF paper chute and stacker. *¹⁷ Requires PaperStream IP 1.60.0 or earlier and PaperStream Capture 2.8.2 or earlier. *¹⁸ Functions equivalent to those offered by PaperStream IP may not be available with the Image Scanner Driver for macOS/Linux or WIA Driver. *¹⁹ Refer to the fi Series Support Site for driver/software downloads and full lineup of all supported operating system versions.

Trademarks

ABBYY™ FineReader™ Engine © ABBYY. OCR by ABBYY. ABBYY and FineReader are trademarks of ABBYY Software, Ltd. which may be registered in some jurisdictions. ISIS is a trademark of Open Text. Microsoft, Windows, and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. macOS is a trademark of Apple Inc., registered in the U.S. and other countries. Linux is the registered trademark of Linus Torvalds in the U.S. and other countries. Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies.

Safety Precautions

Be sure to carefully read all safety precautions prior to using this product and use this device as instructed. Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product. Be sure to limit the use of this product to listed power ratings.

ENERGY STAR®

PFU Limited, a Fujitsu company, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.

Specifications are subject to change without notice. Visit your local Fujitsu website for more information.

Contact

| | | | | | |
|--|--|---|--|---|--|
| Indonesia PT Fujitsu Indonesia Tel: +62 21 570 9330 marketing_fid@fujitsu.com www.fujitsu.com/id/scanners | Malaysia Fujitsu (Malaysia) Sdn Bhd Tel: +603 8230 4188 askfujitsu.my@fujitsu.com www.fujitsu.com/my/scanners | Philippines Fujitsu Philippines, Inc. Tel: +63 2 841 8488 info@ph.fujitsu.com www.fujitsu.com/ph/Drivers | Singapore Fujitsu Asia Pte Ltd Tel: +65 6512 7555 scanner@fujitsu.com www.fujitsu.com/sg/scanners | Thailand Fujitsu (Thailand) Co., Ltd. Tel: +66 2 302 1500 info.th@fujitsu.com www.fujitsu.com/th/en/scanners | Vietnam Fujitsu Vietnam Limited Tel: + 84 4 2220 3113 sales-vn@fujitsu.com www.fujitsu.com/vn/en/scanners |
|--|--|---|--|---|--|